



Colphene
Flam 180



THE SOLUTION FOR PLAZA DECK WATERPROOFING

COLPHENE FLAM 180 is the ideal solution for plaza deck waterproofing. The membrane has an excellent puncture and tear resistance due to its non-woven polyester reinforcement. The surface and the underface are covered with a thermofusible plastic film. In addition to ensure plaza deck waterproofing, COLPHENE FLAM 180 is used as a waterproofing membrane on concrete foundation walls and other below grade application.

SURFACE PREPARATION

COLPHENE FLAM 180 must always be installed on clean, dry and solid substrates, which have been primed with ELASTOCOL 500.

COLPHENE FLAM 180

THICKNESS	3.0 mm (120 mil)
DIMENSION	1 × 10 m (3.3 × 33 ft)
SURFACE	Thermofusible plastic film
UNDERFACE	Thermofusible plastic film

COMPLEMENTARY PRODUCT

ELASTOCOL 500 is a primer made from bitumen, fast evaporating solvents and adhesive enhancing additives. It is required to prime most surfaces such as concrete and metal substrates in order to improve the adhesion of torch-applied waterproofing membranes.



Excellent puncture and tear resistance

Easy to install

Can be installed in cold weather

Since 1908, SOPREMA has specialized in the manufacture of waterproofing products for the construction and civil engineering fields.



1.877.MAMMOUTH
www.soprema.ca